

ENCLOSED CONDENSING UNITS

PRODUCT FEATURES

- Easy install
- Fully wired
- Local parts
- Custom options
- Built to last
- Large condensers
- Powder coated
- Blue fins



TECH DATA

EMF26-1H

UNIT MODEL	EMF26-1H		
STOCK CODE	AGQ0730		
COMPRESSOR TYPE	Copeland Scroll		
COMPRESSOR		FANS	
MODEL	QTY	SIZE	POLES
ZB26KQE-PFJ	1	450	4

AMBIENT °C	R134a COOLING CAPACITY (kW)				
	-15	-10	-5	0	5
35°C	3.1	3.8	4.5	5.4	6.5
40°C	2.7	3.3	4	4.8	5.7
45°C	2.4	2.9	3.5	4.2	5


Ratings based on 11 k suction superheat/3k subcooling
 For 38° ambient ratings - multiply 35° by 0.94
 For 43° ambient ratings - multiply 40° by 0.94

To avoid compressor damage, suction superheat must be equal to 10k

ELECTRICAL						
COMPRESSOR		FAN			OVERALL	
VOLT.	MRA	VOLT.	MRA (EACH)	MRA (TOTAL)	VOLT.	MRA
240	18	240	1.75	1.75	240	19.75

DIMENSIONS (MM)					CONNECTIONS	
(W)	(D)	(H)	KG	(P)	LIQUID	SUCTION
1235	605	900	93	450	1/2	3/4

NOISE		RECEIVER	FITTED HP/LP
dBA -10m	dBA -3m	VOLUME (L)	
50	60	4	Auto/Manual



FITTED WITH

- Fan cycle HP
- Drier & sight glass
- Oil sep
- HPLP
- CCH
- NRV

AVAILABLE OPTIONS *

- Fan speed controller
- Solenoid valve
- Suction accumulator
- Isolator

* Please note additional fitted options may change the unit dimensions.