



Reciprocating compressor, MTZ72HN4CVE

MTZ72-4VI [↗](#)

Refrigerants: R404A; R407C; R452A; R407A; R134a; R454C; R407F; R513A; R448A; R454A; R455A; R449A, Segment usage: Refrigeration MT, Compressor power supply [V]: 400/3/50 460/3/60, Packing format: Single pack

Where to buy [↗](#)

Product specifications

Characteristic	Value
Approval	CE, UL, UKCA
Brand technique	Reciprocating compressor
Capacity Control	Fixed speed
CE mark	Yes
China RoHS compliance	Yes with exemptions
China RoHS exemption clause	7.1, 7.3
Colour	Blue
Compressor power supply [V]	400/3/50 460/3/60
Configuration code	Single
Connection type	Rotolock
Contains batteries	No
CoolselectorFilter	Active models
Cylinder	2
Description	MTZ072-4
DG Indicator Profile	Not relevant for dangerous goods
Diameter [mm]	288 mm
Discharge connection height [mm]	74 mm
Discharge connection pipe size [in]	3/4 in
Discharge connection size [in]	1-1/4 in
Drawing number	8502012g



Characteristic	Value
Economizer	No
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(a)-I, 6(c)
Factory HP [bar]	25 bar
Factory LP [bar]	25 bar
Family	MTZ
Fitting remark	(shipped with rotolock version only)
Fitting sleeve	ODF
Fitting standard	Rotolock
Frequency [Hz]	50/60
Gauge port HP	None
Gauge port LP	Schrader
Glass mounting	Threaded
Glass torque [Nm]	50 N-m
GP LP torque [Nm]	15 N-m
High Side TS Max	150.0 °C
High Side TS Min	-35.0 °C
High Side Volume	0.6 L
High value of nominal voltage at 50Hz [V]	400 V
High value of nominal voltage at 60Hz [V]	460 V
High value of voltage range at 50Hz [V]	440 V
High value of voltage range at 60Hz [V]	506 V
Identical product	MTZ72-4VM
In scope of WEEE	No
IP protection class	IP55 (with cable gland)
Low Side TS Max	50.0 °C
Low Side TS Min	-35.0 °C
Low Side Volume	16.5 L
Low value of nominal voltage at 50Hz [V]	380 V



Characteristic	Value
Low value of nominal voltage at 60Hz [V]	460 V
Low value of voltage range at 50Hz [V]	340 V
Low value of voltage range at 60Hz [V]	414 V
LRA	85 A
Material Description	COMPRESSOR OSG-EQUAL MULTIREF
Max pressure (PS) - high side	29.40 bar
Max pressure (PS) - low side	22.60 bar
Maximum Operating Current [MOC]	14 A
MCC	19 A
Model number	MTZ72HN4CVE
Motor protection	Internal overload protector
Mounting torque [Nm]	15.00 N-m
Network power supply [V/Ph/Hz]	380-415/3/50 460/3/60
Number of starts per hour [Max]	12
Oil charge [L]	1.80 L
Oil equalization	3/8" flare SAE
Oil equalization torque [Nm]	30 N-m
Oil level switch	None
Oil reference	175PZ
Packaging height [mm]	455 mm
Packaging length [mm]	395 mm
Packaging weight [Kg]	41 kg
Packaging width [mm]	365 mm
Packing format	Single pack
Packing quantity	1
Phase	3
Power connections	Spade
Product group	Hermetic compressors
Product line	Commercial Compressors

Characteristic	Value
Product name	Reciprocating compressor MTZ
Product Type	MTZ072
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Refrigerant charge [kg] [Max]	5.00 kg
Refrigerants	R134a, R404A, R407A, R407C, R407F, R448A, R449A, R452A, R513A, R454A, R454C, R455A
Rotational speed at 50Hz [rpm]	2900 rpm
Rotational speed at 60Hz [rpm]	3500 rpm
SCIP dossier no.	9b3fb119-9852-486a-92dd-53aa9c96fd3b
Segment usage	Refrigeration MT
Shipped fittings	Suction and discharge solder sleeves, rotolock nuts and gaskets
Shipped instructions	Installation instructions
Shipped mounting	Mounting kit with grommets, bolts, nuts, sleeves and washers
Shipped oil	Initial oil charge
Suction connection height [mm]	265 mm
Suction connection material	-
Suction connection pipe size [in]	7/8 in
Suction connection size [in]	1-3/4 in
Swept volume [cm ³]	120.94 cm ³
Technology	Reciprocating
Test dif [bar] [Max]	30 bar
Test HP [bar] [Max]	30.0 bar
Test LP [bar] [Max]	25.0 bar
Torque earth [Nm]	3.00 N-m
Torque power [Nm]	3.00 N-m
Total height [mm]	413.0 mm
U.S. EPA label	For installations using U.S. EPA restricted refrigerants, this product may be used for servicing existing equipment only
UL mark	Yes

Characteristic	Value
Winding resistance for three-phase compressors with identical windings [Ohm]	1.85 Ohm

General specifications

Characteristic	Value
Gross weight	42.42 Kilogram
Net weight	39.93 Kilogram
Volume	61.548 Liter
EAN/UPC	5702428887946
Proposition 65	Cancer and Reproductive Harm

For the most current information and other product assets, please use this link to visit the product page on Design Center [↗](#)