



Reciprocating compressor, NTZ215A4LR1B

120F0240 [↗](#)

Refrigerants: R404A; R452A, Segment usage: Refrigeration LT, Compressor power supply [V]: 400/3/50 460/3/60, Packing format: Single pack

Where to buy [↗](#)

Product specifications

Characteristic	Value
Approval	CE, UKCA
Brand technique	Reciprocating compressor
Capacity Control	Fixed speed
CE mark	Yes
China RoHS compliance	Yes with exemptions
China RoHS exemption clause	7.1, 7.3, 8.1, 8.3.1
Colour	Blue
Compressor power supply [V]	400/3/50 460/3/60
Configuration code	Single
Connection type	Rotolock
Contains batteries	No
CoolselectorFilter	Active models
Cylinder	4
Description	NTZ215-4B
DG Indicator Profile	Not relevant for dangerous goods
Diameter [mm]	352 mm
Discharge connection height [mm]	125 mm
Discharge connection pipe size [in]	3/4 in
Discharge connection size [in]	1-1/4 in
Drawing number	8504010f
Economizer	No



Characteristic	Value
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(a)-I, 6(c), 7(a), 7(c)-I
Factory HP [bar]	25 bar
Factory LP [bar]	25 bar
Family	NTZ
Fitting remark	(shipped with rotolock version only)
Fitting sleeve	ODF
Fitting standard	Rotolock
Frequency [Hz]	50/60
Gauge port HP	None
Gauge port LP	Schrader
Glass mounting	Threaded
Glass torque [Nm]	50 N-m
GP LP torque [Nm]	15 N-m
High Side TS Max	150.0 °C
High Side TS Min	-35.0 °C
High Side Volume	1.2 L
High value of nominal voltage at 50Hz [V]	400 V
High value of nominal voltage at 60Hz [V]	460 V
High value of voltage range at 50Hz [V]	460 V
High value of voltage range at 60Hz [V]	506 V
Identical product	120F0241
In scope of WEEE	No
IP protection class	IP54 (with cable gland)
Low Side TS Max	50.0 °C
Low Side TS Min	-35.0 °C
Low Side Volume	31.0 L
Low value of nominal voltage at 50Hz [V]	380 V
Low value of nominal voltage at 60Hz [V]	460 V



Characteristic	Value
Low value of voltage range at 50Hz [V]	340 V
Low value of voltage range at 60Hz [V]	414 V
LRA	74 A
Material Description	COMPRESSOR NTZ215-4LR1-SINGLE RECIP
Max pressure (PS) - high side	28.50 bar
Max pressure (PS) - low side	22.60 bar
Maximum Operating Current [MOC]	14.9 A
MCC	22.3 A
Model number	NTZ215A4LR1B
Motor protection	Internal overload protector
Mounting torque [Nm]	15.00 N-m
Network power supply [V/Ph/Hz]	380-415/3/50 460/3/60
Number of starts per hour [Max]	12
Oil charge [L]	3.90 L
Oil equalization	3/8" flare SAE
Oil equalization torque [Nm]	30 N-m
Oil level switch	None
Oil reference	175PZ
Packing format	Single pack
Packing quantity	1
Phase	3
Power connections	Screw connectors 10-32 UNF x 9.5
Product group	Hermetic compressors
Product line	Commercial Compressors
Product name	Reciprocating compressor NTZ
Product Type	NTZ215
REACH Candidate List substances	Lead (CAS no. 7439-92-1), Diboron trioxide (B2O3, CAS no. 1303-86-2)
Refrigerant charge [kg] [Max]	10.00 kg
Refrigerants	R404A, R452A



Characteristic	Value
Rotational speed at 50Hz [rpm]	2900 rpm
Rotational speed at 60Hz [rpm]	3500 rpm
SCIP dossier no.	6971587b-85b6-4808-886d-274e8a9998d4
Segment usage	Refrigeration LT
Shipped fittings	Suction and discharge solder sleeves, rotolock nuts and gaskets
Suction connection height [mm]	233 mm
Suction connection material	-
Suction connection pipe size [in]	1-1/8 in
Suction connection size [in]	1-3/4 in
Swept volume [cm3]	215.00 cm ³
Technology	Reciprocating
Test dif [bar] [Max]	30 bar
Test HP [bar] [Max]	30.0 bar
Test LP [bar] [Max]	25.0 bar
Torque earth [Nm]	3.00 N-m
Torque power [Nm]	3.00 N-m
Total height [mm]	519.0 mm
U.S. EPA label	For installations using U.S. EPA restricted refrigerants, this product may be used for servicing existing equipment only
Winding resistance for three-phase compressors with identical windings [Ohm]	2.23 Ohm

General specifications

Characteristic	Value
Gross weight	68.25 Kilogram
Net weight	63.67 Kilogram
Volume	100.754 Liter
EAN/UPC	5702428521123
Proposition 65	Cancer and Reproductive Harm

For the most current information and other product assets, please use this link to visit the product page on Design Center [🔗](#)