



Reciprocating compressor, NTZ048A4LR1B

[120F0226](#)

Refrigerants: R404A; R452A; R454C; R455A, Segment usage: Refrigeration LT, Compressor power supply [V]: 400/3/50 460/3/60, Packing format: Single pack

[Where to buy](#)

Product specifications

Characteristic	Value
Approval	CCC, CE, UL, UKCA
Brand technique	Reciprocating compressor
Capacity Control	Fixed speed
CE mark	Yes
China RoHS compliance	Yes with exemptions
China RoHS exemption clause	7.1, 7.3
Colour	Blue
Compressor power supply [V]	400/3/50 460/3/60
Configuration code	Single
Connection type	Rotolock
Contains batteries	No
CoolselectorFilter	Active models
Cylinder	1
Description	NTZ048-4B
DG Indicator Profile	Not relevant for dangerous goods
Diameter [mm]	224 mm
Discharge connection height [mm]	68 mm
Discharge connection pipe size [in]	1/2 in
Discharge connection size [in]	1 in
Drawing number	8501026f

Characteristic	Value
Economizer	No
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(a)-I, 6(c)
Factory HP [bar]	25 bar
Factory LP [bar]	25 bar
Family	NTZ
Fitting remark	(shipped with rotolock version only)
Fitting sleeve	ODF
Fitting standard	Rotolock
Frequency [Hz]	50/60
Gauge port HP	None
Gauge port LP	Schrader
Glass mounting	Threaded
Glass torque [Nm]	50 N-m
GP LP torque [Nm]	15 N-m
High Side TS Max	150.0 °C
High Side TS Min	-35.0 °C
High Side Volume	0.3 L
High value of nominal voltage at 50Hz [V]	400 V
High value of nominal voltage at 60Hz [V]	460 V
High value of voltage range at 50Hz [V]	440 V
High value of voltage range at 60Hz [V]	506 V
Identical product	120F0227
In scope of WEEE	No
IP protection class	IP55 (with cable gland)
Low Side TS Max	50.0 °C
Low Side TS Min	-35.0 °C
Low Side Volume	7.5 L
Low value of nominal voltage at 50Hz [V]	380 V



Characteristic	Value
Low value of nominal voltage at 60Hz [V]	460 V
Low value of voltage range at 50Hz [V]	340 V
Low value of voltage range at 60Hz [V]	414 V
LRA	16 A
Material Description	NTZ048-4LR1-SINGLE
Max pressure (PS) - high side	28.50 bar
Max pressure (PS) - low side	22.60 bar
Maximum Operating Current [MOC]	3.8 A
MCC	4.8 A
Model number	NTZ048A4LR1B
Motor protection	Internal overload protector
Mounting torque [Nm]	15.00 N-m
Network power supply [V/Ph/Hz]	380-415/3/50 460/3/60
Number of starts per hour [Max]	12
Oil charge [L]	0.95 L
Oil equalization	3/8" flare SAE
Oil equalization torque [Nm]	30 N-m
Oil level switch	None
Oil reference	175PZ
Packaging height [mm]	370 mm
Packaging length [mm]	385 mm
Packaging width [mm]	285 mm
Packing format	Single pack
Packing quantity	1
Phase	3
Power connections	Spade
Product group	Hermetic compressors
Product line	Commercial Compressors
Product name	Reciprocating compressor NTZ

Characteristic	Value
Product Type	NTZ048
REACH Candidate List substances	Lead (CAS no. 7439-92-1), Diboron trioxide (B2O3, CAS no. 1303-86-2)
Refrigerant charge [kg] [Max]	2.50 kg
Refrigerants	R404A, R452A, R454C, R455A
Rotational speed at 50Hz [rpm]	2900 rpm
Rotational speed at 60Hz [rpm]	3500 rpm
SCIP dossier no.	5a332c1b-1d1b-4998-8115-d0929877ecb4
Segment usage	Refrigeration LT
Shipped fittings	Suction and discharge solder sleeves, rotolock nuts and gaskets
Shipped instructions	Installation instructions
Shipped mounting	Mounting kit with grommets, bolts, nuts, sleeves and washers
Shipped oil	Initial oil charge
Suction connection height [mm]	263 mm
Suction connection material	-
Suction connection pipe size [in]	5/8 in
Suction connection size [in]	1-1/4 in
Swept volume [cm ³]	48.00 cm ³
Technology	Reciprocating
Test dif [bar] [Max]	30 bar
Test HP [bar] [Max]	30.0 bar
Test LP [bar] [Max]	25.0 bar
Torque earth [Nm]	3.00 N-m
Torque power [Nm]	3.00 N-m
Total height [mm]	333.0 mm
U.S. EPA label	For installations using U.S. EPA restricted refrigerants, this product may be used for servicing existing equipment only
UL mark	Yes
Winding resistance for three-phase compressors with identical windings [Ohm]	11.55 Ohm

General specifications

Characteristic	Value
Gross weight	22.75 Kilogram
Net weight	21 Kilogram
Volume	37.734 Liter
EAN/UPC	5702428521086
Proposition 65	Cancer and Reproductive Harm

For the most current information and other product assets, please use this link to visit the product page on Design Center [🔗](#)